

# MATERIAL SAFETY DATA SHEET

THE OUTLAW® OCTANE BOOSTER

## 1. PRODUCT AND COMPANY IDENTIFICATION

MSDS Number: 14091

Version Date: 4/11/2002

**Product Name:** THE OUTLAW® OCTANE BOOSTER

**Product Use:** Octane booster

**Synonyms:** S295, S296, 23225

### Manufacturer

Pennzoil-Quaker State Company  
Outlaw Products  
P.O. Box 2967  
Houston, TX 772522967  
USA

### Phone Numbers

**Medical Emergency:** 1-800-546-6040

**Transportation Emergency (USA):** 1-800-535-5053

**Transportation Emergency (International):**

1-352-323-3500 (Call Collect)

**MSDS Assistance:** 1-800-546-6227

**Fax On Demand:** 1-800-546-6227

**Technical Assistance:** 1-800-458-4998

**Customer Service:** 1-800-468-8397

**Fax Number:** 713-217-3181

**Internet Address:** www.MSDS.PZLQS.com

## 2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
KEROSENE	8008-20-6	95 - 100	Yes
FUEL ADDITIVE	TRADESECRET	1 - 5	No
STABILIZER	TRADESECRET	< 1	No

This product is **HAZARDOUS** according to OSHA 29 CFR 1910.1200.

### Hazards:

**Flammable/Combustible**   X   **Acute Toxin**   X   **Chronic Toxin**        **Carcinogen**         
**Pressure**        **Reactive**        **Exposure Limit**        **Target Organ**        **Other**       

**Other:** No information available

## 3. HAZARDS IDENTIFICATION

### Emergency and Hazards Overview

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

**NFPA Ratings:** **Health**   1   **Flammability**   2   **Reactivity**   0  

**Primary Route of Exposure:** **Skin**   X   **Inhalation**   X   **Eye**       

### Health Effect Information

**Eye Contact:** Avoid eye contact. This product is minimally irritating to the eyes upon direct contact. Based on testing of similar products and/or components. This product has a low vapor pressure and is not expected to present a hazard to the eyes at ambient conditions. Exposure to high concentrations of vapors may be irritating to the eyes.

**Skin Contact:** Avoid skin contact. This product is minimally irritating to the skin upon direct contact. Based on testing of similar products and/or components. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. See Section 11 - Toxicological Information.

**MATERIAL SAFETY DATA SHEET**  
**THE OUTLAW® OCTANE BOOSTER**

**Inhalation:** Avoid prolonged inhalation of mist or vapors. This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. Acute and chronic overexposures may be irritating to the respiratory tract. Severe intoxication may lead to drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea.

**Ingestion:** Do not ingest. Ingestion of small quantities is usually nonfatal unless aspiration occurs. Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage and may be fatal. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting with a further risk of aspiration. Ingestion may cause gastrointestinal distress. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result.

**Medical Conditions Aggravated by Exposure:** Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

**Other:** No information available

---

**4. FIRST AID INFORMATION**

**Eye Contact:** Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

**Skin Contact:** Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. Use a hand or skin lotion to prevent dryness.

**Inhalation:** This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. If victim exhibits signs of vapor intoxication remove to fresh air. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek immediate medical attention.

**Ingestion:** Do not induce vomiting due to aspiration hazard. If vomiting occurs lower head below knees to avoid aspiration. Seek immediate medical attention.

**Notes to Physician:** No information available

**Other:** No information available

---

**5. FIRE AND EXPLOSION INFORMATION****Flammable Properties**

**Flash Point:** >100 F, >37.8 C

**Test Method:** ASTM D-56 (T.C.C.)

**Flammable Limits in Air**

**Upper Percent:** 5%

**Lower Percent:** 0.7%

**Autoignition Temperature:** 410 F, 210 C

**Test Method:** No information available

**NFPA Classification:** Class II combustible liquid

**Extinguishing Media:** Use dry chemical, foam, or carbon dioxide.

**Fire Fighting Measures**

**Special Fire Fighting Procedures and Equipment:** Water may be ineffective but can be used to cool containers exposed to heat or flame to prevent vapor pressure buildup and possible container rupture.

**Unusual Fire and Explosion Conditions:** Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

**Hazardous Combustion By-Products:** None

**Other:** No information available

---

**6. ACCIDENTAL RELEASE MEASURES**

**Personnel Safeguards:** Remove all sources of ignition. Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10. Provide adequate ventilation during clean-up.

**Regulatory Notifications:** Notify appropriate authorities of spill.

**Containment and Clean up:** Contain spill immediately. Do not allow spill to enter sewers or watercourses. Absorb with solvent absorbent material. Large spills may be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

**Other:** No information available

---

**7. HANDLING AND STORAGE INFORMATION**

**Handling:** Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106--Flammable and Combustible Liquids.

**Storage:** Do not transfer to unmarked containers. Store in a cool, well ventilated area in closed containers away from heat, sparks, open flame or oxidizing materials.

**Empty Container Warnings**

**Drums:** Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed. Empty containers retain product residue and can be dangerous. DO NOT PRESSURIZE, CUT WELD, BRAZE SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

**Plastic:** Do not reuse this container. Empty container may retain product residues.

**Other:** No information available

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION****Exposure Limits and Guidelines**

This product does not contain any components with OSHA or ACGIH exposure limits.

**Personal Protective Equipment**

**Eye/Face Protection:** Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

**MATERIAL SAFETY DATA SHEET**  
**THE OUTLAW® OCTANE BOOSTER**

**Skin Protection:** No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated.

**Respiratory Protection:** Respiratory protection is not required under conditions of normal use. If concentrations are greater than the limits in Sections 8 or 3, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

**Personal Hygiene:** Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

**Engineering Controls / Work Practices**

**Ventilation:** If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure or flammable limits. See also Fire and Explosion Information in Section 5.

**Other:** As a precaution, all exposure to mists and vapors of petroleum products should be minimized. The OSHA permissible exposure limit (PEL) and ACGIH threshold limit value (TLV) for oil mist is 5 mg/m<sup>3</sup>. Chronic exposures below 5 mg/m<sup>3</sup> are without significant health risks. The ACGIH short-term exposure limit (STEL) for oil mist is 10 mg/m<sup>3</sup>. The OSHA PEL for petroleum distillates is 2000 mg/m<sup>3</sup>. NIOSH recommends a 10-hour TWA of 100 mg/m<sup>3</sup> for kerosene.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b> Clear, brown	
<b>Odor:</b> Aromatic	<b>Vapor Pressure:</b> < 1 mm Hg @ 68 F
<b>Physical state:</b> Liquid	<b>Vapor Density (air=1):</b> 4.7
<b>pH:</b> No data available	<b>Percent Volatile by Volume:</b> 99
<b>Boiling Point:</b> 280 - 300 F, 137.8 - 148.9 C	<b>Volatile Organic Content:</b> No data available
<b>Melting Point:</b> No data available	<b>Molecular Weight:</b> No data available
<b>Specific Gravity:</b> 0.81	<b>Average Carbon Number:</b> No data available
<b>Pour Point:</b> -30 F, -34.4 C	<b>Viscosity @ 100 F:</b> No data available
	<b>Viscosity @ 40 C:</b> No data available
<b>Solubility in Water:</b> Negligible in water	
<b>Octanol / Water Coefficient: Log K<sub>ow</sub> =</b> No data available	

---

**10. STABILITY AND REACTIVITY INFORMATION**

**Chemical Stability:** Stable

**Conditions to Avoid:** High heat and open flames.

**Incompatible Materials to Avoid:** May react with strong oxidizing agents.

**Other:** No information available

---

**11. TOXICOLOGICAL INFORMATION**

**Primary Eye Irritation:** No information available

**Primary Skin Irritation:** No information available

**Acute Dermal Toxicity:** No information available

**Subacute Dermal Toxicity:** No information available

**Dermal Sensitization:** No information available

**Inhalation Toxicity:** No information available

**Inhalation Sensitization:** No information available

**Oral Toxicity:** No information available

**Mutagenicity:** No information available

**Carcinogenicity:** The International Agency for Research on Cancer (IARC) has concluded that light and intermediate middle distillates are Group 3 substances, "not classifiable as to their carcinogenicity to humans," based on inadequate human and inadequate animal evidence.

**Reproductive and Developmental Toxicity:** No information available

**Teratogenicity:** No information available

**Immunotoxicity:** No information available

**Neurotoxicity:** No information available

**Other:** No information available

---

## 12. ECOLOGICAL INFORMATION

**Aquatic Toxicity:** No information available

**Terrestrial Toxicity:** No information available

**Chemical Fate and Transport:** No information available

**Other:** No information available

---

## 13. DISPOSAL INFORMATION

**Regulatory Information:** All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled.

**Waste Disposal Methods:** Waste material may be landfilled or incinerated at an approved facility. Materials should be recycled if possible.

**Other:** No information available

---

## 14. TRANSPORTATION INFORMATION

**U.S. Department of Transportation (DOT)**

**Highway / Rail (Bulk):** Not Regulated

**Highway / Rail (Non-Bulk):** Not Regulated

**MATERIAL SAFETY DATA SHEET**

THE OUTLAW® OCTANE BOOSTER

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping descriptions.

**International Information**

Vessel: IMDG Regulated:   X   IMDG Not Regulated:         
Air: ICAO Regulated:   X   ICAO Not Regulated:       

Other: No information available

---

**15. Regulatory Information**

**Regulatory Lists Searched:** The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

**Health & Safety:** 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

**Environmental:** 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depleters, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

**International:** 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification

**State Lists:** 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

**Inventories:** 80 - Canada - Domestic substances , 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA , 85 - China Inventory

**Regulatory Search Results:**

KEROSENE: 17, 23, 50, 61, 63, 66, 67, 68, 69, 80, 81, 83, 84, 85

**U.S. TSCA Inventory:** All components of this material are on the US TSCA Inventory.

**SARA Section 313:** Consumer products are not regulated under SARA, Title III, Section 313.

**IARC:** No information available

**SARA 311 / 312 Categories**

Acute:   X   Chronic:        Fire:   X   Pressure:        Reactive:         
Not Regulated:       

**Canadian WHMIS Classification**

Class B - Flammable and Combustible Material, Division 3, Combustible Liquid  
Class D - Poisonous and infectious material, Division 2B, Toxic Material

**MATERIAL SAFETY DATA SHEET**  
**THE OUTLAW® OCTANE BOOSTER****European Union Classification****Hazard Symbols:**

Dangerous for the environment / N / dead tree and fish in square  
Harmful / Xn / X in square.

**Risk Phrases:**

R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.  
R65: Harmful: may cause lung damage if swallowed.  
R66: Repeated exposure may cause skin dryness or cracking.

**Safety Phrases:**

S2: Keep out of the reach of Children.  
S23: Do not breathe gas/fumes/vapour/spray.  
S24: Avoid contact with skin.  
S61: Avoid release to the environment. Refer to special instructions/Safety data sheet.  
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Other:** No information available

---

**16. OTHER INFORMATION****Health and Environmental Label Language**

Front Label:

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

Read carefully other cautions on back.

Back Label:

DANGER: Contains petroleum middle distillates. Prolonged and repeated skin contact may cause drying of skin.

PRECAUTIONARY MEASURES: Keep away from heat and flames. Avoid breathing of mists and vapors. Use only in well ventilated areas. Avoid repeated and prolonged skin contact. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If inhaled, breathe fresh air. For skin or eye contact, wash thoroughly with water.

KEEP OUT OF REACH OF CHILDREN.

**MSDS Revisions**

**Previous Version Date:** 5/29/2001

**Previous Version Information**

Section 2. Component Information - changed OSHA Hazards

Section 3. Hazards Identification - changed primary route of exposure.

**Other**

No information available

**Prepared By:**

Pennzoil-Quaker State Company  
Environmental, Safety, Health, & DOT Compliance  
P.O. Box 2967  
Houston, TX 77252-2967 USA